



Orchard Audio

Valencia Instructions

Warnings:

- Do not use with single ended headphones and adapters.
 - This will cause damage that will not be covered under warranty.
- Due to the bridged amplifier design, both speaker terminals are hot when the amplifier is on.
 - Do not connect any of the speaker terminals to GND or EARTH
 - When connecting to subwoofer's high-level input(s), double check this is supported. Contact us if not sure.
- This is an extremely powerful amplifier with no volume control. To not damage hearing start with your source device at a very low volume and increase as needed.

Notes:

- Use provided adapter for 4.4mm balanced headphone plugs
- The amplifier uses a universal AC input power supply and will function with all voltages between 95 and 264 VAC.
- Do not connect headphones and speakers at the same time.
- No user-serviceable parts – tampering with the amplifier will void the warranty

To Turn the Amplifier On:

1. Connect speakers or headphones
2. Connect XLR inputs
3. Make sure the power switch is in the off position (0).
4. Connect power cord
5. Turn the power switch to the on position (I).
6. Push the button on the front of the unit and it will light up.

To Turn the Amplifier Off:

1. Push the button on the front of the unit and it's light will turn of. This puts the amplifier into a low power standby state. The amplifier can be left on in this state.
2. Turn the power switch to the off position (0).
3. Wait at least 10 seconds
4. Remove/swap connections if needed.

How do you like them apples?