



Orchard Audio

Valencia MG Instructions

Warnings:

- Do not use with single-ended headphones and adapters.
 - This will cause damage that will not be covered under warranty.
- Due to the bridged amplifier design, both speaker terminals are hot when the amplifier is on.
 - Do not connect any of the speaker terminals to GND or EARTH
 - When connecting to a subwoofer's high-level input(s), double-check this is supported. Contact us if not sure.
- This is an extremely powerful amplifier with no volume control. To not damage hearing, start with your source device at a very low volume and increase as needed.

Notes:

- Use the provided adapter for 4.4mm balanced headphone plugs
- The amplifier uses a universal AC input power supply and will function with all voltages between 95 and 264 VAC.
- Do not connect headphones and speakers at the same time.
- No user-serviceable parts – tampering with the amplifier will void the warranty

Modifying Gain – Watch [this video](#) to see how to change the gain between the 14dB and 0dB settings.

To Turn the Amplifier On:

1. Connect speakers or headphones
2. Connect XLR inputs
3. Make sure the power switch is in the off position (O).
4. Connect the power cord
5. Turn the power switch to the on position (I).
6. Push the button on the front of the unit and it will light up.

To Turn the Amplifier Off:

1. Push the button on the front of the unit, and its light will turn off. This puts the amplifier into a low-power standby state. The amplifier may be left on in this state.
2. Turn the power switch to the off position (O).
3. Wait at least 10 seconds
4. Remove/swap connections if needed.

How do you like them apples?